



# TL-D Standard Colours

## TL-D 30W/54-765 1SL/25

TL-D Standard Colors lamps (tube diameter of 26 mm) create atmospheres from warm white to cool daylight. Lamps with moderate efficacy and color rendering.

### Product data

General Information	
Cap-Base	G13 [ Medium Bi-Pin Fluorescent]
Life To 10% Failures (Nom)	10000 h
Life to 50% Failures (Nom)	13000 h

Light Technical	
Color Code	54-765
Luminous Flux (Nom)	1825 lm
Color Designation	Cool Daylight
Lumen Maintenance 10000 h (Nom)	75 %
Lumen Maintenance 2000 h (Nom)	90 %
Lumen Maintenance 5000 h (Nom)	80 %
Correlated Color Temperature (Nom)	6200 K
Color Rendering Index (Nom)	72

Operating and Electrical	
Power (Nom)	30.0 W
Lamp Current (Nom)	0.360 A
Voltage (Nom)	98 V

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy Efficiency Label (EEL)	B
Mercury (Hg) Content (Nom)	8.0 mg
Energy Consumption kWh/1000 h	36 kWh

Product Data	
Full product code	871869648774700
Order product name	TL-D 30W/54-765 1SL/25
EAN/UPC - Product	8718696487747
Order code	928025405451
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	928025405451
Net Weight (Piece)	148.900 g
ILCOS Code	FD-30/62/2A-E-G13

### Warnings and Safety

# TL-D Standard Colours

## Dimensional drawing




TL-D 30W/54-765


### Product

TL-D 30W/54-765 1SL/25

## Photometric data




LDPB\_TL-DSTD\_54-765-Spectral power distribution B/W




LDPO\_TL-DSTD\_54-765-Spectral power distribution Colour

## Lifetime



LDLE\_TL-DSTD\_0001-Life expectancy diagram



LDLE\_TL-DSTD\_0002-Life expectancy diagram

## TL-D Standard Colours

### Lifetime



LDLM\_TL-DSTD\_0001-Lumen maintenance diagram

