



Economy stick

Economy Stick 18W WW E27 220-240 1PF/6

Entry non-covered energy saving lamp, Long life with low energy consumption. Product consists of Philips quality at everyday low price

Product data

| General Information | |
|---------------------------------------|---------------------|
| Cap-Base | E27 [E27] |
| Nominal Lifetime (Nom) | 6000 h |
| Switching Cycle | 6000X |
| | |
| Light Technical | |
| Color Code | 827 [CCT of 2700K] |
| Luminous Flux (Nom) | 1100 lm |
| Luminous Flux (Rated) (Nom) | 1100 lm |
| Color Designation | Warm White (WW) |
| Lumen Maintenance 2000 h (Nom) | 88 % |
| Chromaticity Coordinate X (Nom) | 463 |
| Chromaticity Coordinate Y (Nom) | 420 |
| Correlated Color Temperature (Nom) | 2700 K |
| Luminous Efficacy (rated) (Nom) | 61 lm/W |
| Color Rendering Index (Nom) | 82 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| | |
| Operating and Electrical | |
| Input Frequency | 50 or 60 Hz |
| Power (Nom) | 18.0 W |
| Lamp Current (Nom) | 130 mA |
| Starting Time (Nom) | 0.3 s |
| Warm Up Time to 60% Light (Min) | 5 s |

| Warm Up Time to 60% Light (Max) | 40 s |
|---------------------------------|--|
| Power Factor (Nom) | 0.6 |
| Voltage (Nom) | 220-240 V |
| | |
| Controls and Dimming | |
| Dimmable | No |
| | |
| Approval and Application | |
| Energy Efficiency Label (EEL) | A |
| Mercury (Hg) Content (Max) | 2.0 mg |
| Mercury (Hg) Content (Nom) | 1.5 mg |
| Energy Consumption kWh/1000 h | 18 kWh |
| | |
| Product Data | |
| Full product code | 871829121677300 |
| Order product name | Economy Stick 18W WW E27 220-240 1PF/6 |
| EAN/UPC - Product | 8718291216773 |
| Order code | 929689116901 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 929689116901 |
| Net Weight (Piece) | 0.070 kg |

Datasheet, 2020, March 19 data subject to change

Economy stick

Dimensional drawing



ESSENNG Erp 18W WW E27 220-240V 50/60Hz

| Product | D (max) | C (max) | F (max) |
|--|---------|---------|---------|
| Economy Stick 18W WW E27 220-240 1PF/6 | 36.0 mm | 143 mm | 48.4 mm |

